

DATA SHEET

Nile NWA 1050 Outdoor Wi-Fi 6 Access Points

OVERVIEW

As today's work and personal connectivity preferences have shifted to wireless access, users demand the best experience possible, whether indoors or outdoors.

Nile's Wi-Fi 6 NWA 1050 outdoor access points (APs) provide high-performance connectivity in a ruggedized IP67-rated package. Nile APs use a radically simplified operational model for any organization with growing mobility requirements. As a key component of the Nile Service Block, the NWA 1050 is an integral part of the Nile Access Service. It offers the industry's first performance guarantees for wireless coverage, network capacity, and system availability.

The Nile Access Service is designed for quick and straightforward activation, ensuring a seamless Day 1 deployment experience. Using an intuitive mobile app and step-by-step guidance for installing and activating APs, installers can set up the network with zero configuration errors.

Wireless features include Orthogonal Frequency Division Multiple Access (OFDMA) and bidirectional multi-user MIMO for enhanced efficiency. A third radio acts as a monitoring sensor to continuously test the Nile Access Service's availability, coverage, and capacity. The RF neighborhood information provided is used to optimize the wireless LAN experience.



nile

DATA SHEET

Nile NWA 1050 Outdoor Wi-Fi 6 Access Points

ADDITIONAL WIFI FEATURES

Transmit beamforming (TxBF)

- Increased signal reliability and range

Target Wake Time (TWT)

- Ideal for IoT devices that communicate infrequently, TWT establishes a schedule for when clients need to communicate with an AP to help improve client power savings and reduce airtime contention with other clients.

Dynamic Frequency Selection (DFS)

- Optimized use of available RF spectrum

Seamless device roaming

- Standards that aid in better Wi-Fi device roaming such as 802.11k, 802.11r, 802.11v

Automatic Channel Planning

- AP radios automatically orchestrate sophisticated auto-channel and power allocation for optimized performance in a given environment. Includes coverage hole detection and auto mitigation.

Optimized connection and QoS

- Features that steer dual-band capable devices to a better frequency/band and move devices that are sticking to APs with lower RSSI to a better AP to ensure an optimum connection.

SECURITY

WPA3 and Enhanced Open

- The latest version of WPA provides support for stronger encryption and authentication for enterprise-protected networks. Enhanced Open offers seamless new security for users connecting to open networks, where each session is automatically encrypted to protect user passwords and data on guest networks.

Secure Management

- Secure connectivity is enforced by a tamper-proof design, allowing management exclusively through the Nile cloud

DATA SHEET

Nile NWA 1050 Outdoor Wi-Fi 6 Access Points

SPECIFICATIONS

Hardware Model	
	NWA1050 - Outdoor Internal Antenna Model
Wi-Fi Radio Specifications	
	Outdoor, Tri-radio <ul style="list-style-type: none">• 5GHz radio, 802.1ax 4x4 MIMO• 2.4GHz 802.11ax 4x4 MIMO• Dual-band capable 3rd radio, 802.11ac
Primary WLAN Radios	
5GHz Radio	4x4 SU-MIMO Capable; DL-MU-MIMO, UL-MU-MIMO, DL-OFDMA, UL-OFDMA capable
2.4GHz Radio	4x4 SU-MIMO Capable; DL-MU-MIMO, UL-MU-MIMO, DL-OFDMA, UL-OFDMA capable
Supported Frequency Bands, Channels, DFS (country specific restrictions apply)	2.400 - 2.4835GHz 5.150-5.250GHz 5.250-5.350GHz 5.470-5.725GHz 5.725-5.850GHz Channel availability depends on configured country (based on regulatory domain Dynamic Frequency Selection (DFS) optimized use of available RF Spectrum)
Transmit power	2.4GHz radio – Max 24dBm (25dBm EIRP), Min 0dBm 5GHz radio – Max 27dBm (27dBm EIRP), Min 0dBm
Third Radio (Monitoring/Sensor)	
	Dual Band capable, 802.11ac, 1x1 radio; Operating Band: Dual band – 2.400-2.4835GHz, 5.150-5.250GHz, 5.250-5.350GHz, 5.470- 5.725GHz, 5.725-5.850GHz
Transmit power	5GHz – Max 22dBm (EIRP); 2.4GHz – 20dBm (EIRP)
Antenna	Omni-directional internal antenna
Ethernet	
Interface	1x 1/2.5/5GbE RJ45 port, with line rate MACSec Support +/-6kV surge protection using GDT/Varistor
Power Sources, power consumption	
	Power over Ethernet: 802.3bt, 802.3at
	Power budget – 35W at full load

DATA SHEET

Nile NWA 1050 Outdoor Wi-Fi 6 Access Points

Mechanical specifications, Enclosure, LEDs, BT/BLT	
	Shock and Vibration resistant Earth Lug for surge arrest grounding GORE TEX vent hole Dimensions: 10.2" x 10.2" x 2.95" (260mm x 260mm x 75mm) Weight: 4.08 lbs (1.85 kg)
Mounting	Outdoor pole mount & Wall mount capable, horizontal and inclined surface mounting with Universal mount kit (tilt/rotate) The pole & wall mount kit will be shipped with the AP
QR Code	QR Code identifier on the enclosure
LED	Single LED with 3 colors: Red, Yellow, Green
Bluetooth	Supported for hardware installation and activation
Environment/Operation Conditions	
IP Rating	IP67
Operating Temperature	-40°C to +65°C
Operating Humidity	5 to 90% Relative Humidity, noncondensing ETS 300 019 class 3.3 Environments
Storage and Transportation Conditions	-40C to +70C; Humidity 5% to 93% non-condensing ETS 300 019 class 2.3 environments
MTBF	495,059 hrs at 77°F (25°C)
Regulatory Compliance	
	Meets required Regulatory Compliance standards applicable to similar products: FCC/IC/CE UL/IEC/EN 60950 Bluetooth SIG Wi-Fi Alliance Certified